





This document is the property of Amphenol Corporation and is delivered on the express condition that it is not to be disclosed, reproduced or used, in whole or in part, for manufacture or sale by anyone other than Amphenol Corporation without its prior consent, & that no right is granted to disclose or to use any information in this document.

Customer drawing



RECOMMENDED P.C.B LAYOUT
(TOLERANCE +/-0.03)

Positions	Dimensions				
	A	B	D	E	F
9	30.81	24.99	16.24	10.96	2.74
15	39.14	33.32	24.56	19.18	2.74
25	53.04	47.04	38.38	33.24	2.77
37	69.32	63.50	54.76	49.86	2.77



REVISIONS				
SYM	ECN	DESCRIPTION	DATE	APPROVED
A			03/14/08	

D-SUB TECHNICAL DATA

SHELL : Steel, 2.5um(100u") min. tin over 1.25um(50u") min. nickel
BODY : Glass filled thermoplastic.
CONTACTS : Phosphor bronze
0.76um(30u") min. gold over 1.25um(50u") min. nickel in mating area,
2.5um(100u") min. tin over 1.25um(50u") min. nickel on termination area
REAR INSERT : Brass, (100u") min. tin over 50u" min. nickel
BOARDLOCK : Brass, (100u") min. tin over 50u" min. nickel
SCREWLOCK : Brass, (100u") min. tin over 50u" min. nickel
ELECTRICAL : Voltage rating: 250 V RMS at 50 Hz
Current rating: 5A per contact
Withstanding Voltage >1000 V RMS at 50 Hz for one minute
Insulation resistance >5000 M Ohms
Contact resistance 20 mOhms max.
CLIMATIC : Temperature range -55 °C up to 155°C
MARKING : Amphenol-...(Series No.)
Manufacturing date
Commercial reference

PRODUCT CODE

L 77SD X XX S A4 CH 4R C309

L: RoHS Compliance

717SD: tinned shell +
dimples for plug

Shell Size: E,A,B,C

Configuration: 9,15,25,37


Contact type:
S:Female

C309: gold plating 30u"

mounting options:
4R=rear insert 4-40

PCB locking type:
grounding tabs+boardlocks

termination:
1A(European)
A4(MIL)

UNLESS OTHERWISE SPECIFIED TOLERANCES		APPROVAL		DATE
U.S.		METRIC		
.X +/-	/	0.50	DRAWN	Sunny Li 03/14/08
.XX +/-		0.30	CHECKED	tk.wang 03/14/08
.XXX +/-		0.20	CHECKED	
FRACTIONS +/-				
ANGLES +/-		2°		
FOR MATERIALS AND FINISHES SEE NOTES				
REMOVE SHARP EDGES				
DIMENSIONS				
U.S.		INCHES		
METRIC		MM		
ANGLE OF PROJECTION				
				

Amphenol

TITLE
D-SUB contacts , SD series

SIZE	DRAWING NO.	REV.
A4	C L77SDXXXSA4CH4RC309	A
SCALE	NONE	SHEET 1 OF 1